

DESCRIPTION

The FD Garage Lighter is a utility ceiling-mount fixture for general applications in parking garages, covered walkways, canopies, designed for easy installation and maintenance. It combines a durable die-cast aluminum housing, high quality shock proof polycarbonate lens with UV inhibitors with the efficacy of LED IP-54 rated.

SPECIFICATION FEATURES

Construction

Die-cast aluminum housing

Controls

Powered by the High Efficient Antron Driver

Electrical:

Long Life LED System complete with Electrical driver to deliver the optimal performance. LED's available in 4000K with typical CRI: 80. Ambient temperatures -40C to 40C. Regular rated 200,000 hours at 85C. Electronic drivers available in 120M and 347 Volt.

Driver and Module Access:

Drivers and Modules can be accessed by removing the lens

Finish:

Polyester powder-coated bronze finish, rust and corrosion proof

Diffusion:

Silicone perimeter lens gasket and closed-cell neoprene housing gasket seals out moisture and contaminants. High quality shock proof polycarbonate lens with UV inhibitors

Mounting:

By pre-positioned recessed knock out on the housing

Compliance:

cETLus and DLC4.0 Qualified

Warranty:

5 years



LED GARAGE LIGHTER

ORDERING CODE, ENERGY AND PERFORMANCE DATA

Model No	Delivered	LM Input Wat	ts Voltage	Color Ter	np. Efficacy Ln	n/W Certification	Status
FDGA-40	LED4K 3956	43	120M	4K	91	cETLus/DLC	Stock
FDGA-40	LED4K 3956	43	347V	4K	91	cETLus/DLC	Stock
FDGA-60	LED4K 5376	56	120M	4K	93	cETLus/DLC	Stock
FDGA-60	LED4K 5376	56	347V	4K	93	cETLus/DLC	Stock


Option: FDYM-2502 Occupancy Sensor

SHIPPING DATA

Model No. Gross Weight per Carton

FFDGA-40LED4K 3.2KG/7lbs

FDGA-40





FDGA-60

