

SKU#101152 FDRD-4-12W-5CCT-120V-WH-R SKU#101153 FDRD-4-12W-5CCT-120V-BK-R

## 4" Recessed Downlight





• BLACK • WHITE

### Decription

4" Recessed Downlight, Round

#### **Features**

- \* IC Rated, Air-Tight & Wet Location No Housing Required
- \* Fast Installation & No Junction Box Needed
- \* Includes two spring loaded clips to attach to any ceiling material.
- \* 10%-100% dimming capability. This fixture is compatible with industry standard forward-phase / reverse-phase and TRIAC/ELV dimmers
- \* Rated for long life over 50,000 hours




















### **DIMENSIONS**



# Cut Hole Size Ø3-3/4" (95mm)



SPECIFICATIONS	
Model	FDRD-4-12W-5CCT-120V-WH-R   FDRD-4-12W-5CCT-120V-BK-R
Watts	12W
CRI	90 Ra+
Color Temperature(K)	Pre-Select 5 CCT 2700K /3000K/3500K/4000K /5000K
Light Ouput(lm)	800lm
Default Driver Input	AC120V, 60Hz
Dimming	Triac Dimming 10-100%
Power Factor	>0.9
Wet Location	Yes
Air Tight / IC Rated	Yes
Operating Temp.	(-4°F~104°F) -20~40°C
Beam Angle	90°

PACKAGE	
Qty/CTN (pcs)	18pcs/CTN

### **INCLUDED IN BOX**

• 4" Recessed Downlight, and Remote Driver



**Extension Cables** 

### **Mounting Plates**



OPTIONAL ACCESSORIES

FD-UNMP (SKU#101078)

Universal Mounting Plate, compatible with 2", 3", 3.5", 4" Light Panel and Downlights

### 10

10ft flexible connector, for use with Gimbal/ Recessed/slim LED fixtures



20ft flexible connector, for use with Gimbal/ Recessed/slim LED fixtures