

DESCRIPTION

The FD LED Small Pack is an economical security accent and perimeter lighting for entranceways, garages and any areas requiring accent Lighting. Photocell installed.

SPECIFICATION FEATURES

Construction

Cast aluminum back plate. A gasket between the back plate and front cover prevents entry of water and contaminants. Injected-molded, one piece, UV stabilized polycarbonate refractor. Integral secondary heat sink to optimize thermal transfer and maximize performance and life of the LED's. Polyester powder-coated finish, rust and corrosion proof, stabilized to extreme climate changes without cracking or peeling. Suitable for damp locations.

Controls:

The FD LED Small Wall Pack is powered bt Antron Drivers for maximum performance and maximum energy savings.

Electrical:

Long Life LED System complete with Electrical driver to deliver the optimal performance. LED's available in 5000k and 4000K with typical CRI: 80. Ambient temperatures -40C to 40C. Regular rated 94,000 hours at 85C. Electronic drivers available in 120M.

Mounting:

The surface mounting and wiring via the two convenient 3/4" knockouts.

Driver and Module Access:

Drivers can be removed by removing two screws that hold the lens and housing to the die-cast base.

Finish:

Durable polycarbonate bronze housing and prismatic lens with a bronze powder painted die-cast aluminum base.

Diffusion:


UV stabilized polycarbonate refractor.


Compliance:

cETLus and DLC4.0 Qualified

Warranty:

5 years







LED SMALL WALL PACK

ORDERING CODE, ENERGY AND PERFORMANCE DATA

 Model No.	Delivered LM	Input Watts	Voltage	Color Temp.	Efficacy Lm/W	Certification	Status
FDWP2-15LED5KP	1856	15	120M	5K	124	cETLus/DLC	Stock
 FDWP2-25LED5KP	3007	24	120M	5K	125	cETLus/DLC	Stock

Note: Comes with Photo-Cell Assembled

FDWP2-15LED5K-120MP is equal to 30W CFL

FDWP2-25LED5K-120MP is equal to 70W CFL

Option: FDDD-Sensor

