

# LED Under Cabinet Light

## FDUC-23-9W-LED

## T5 LED Bar

22 5/8" 9W LED Under Light



### Factory Direct Lighting

100 Shields Court, Markham,  
ON Canada L3R 9T5

Tel: 905-944-1210 • 1-855-533-0743 |

Toll Fax: 1-855-533-3294

<http://www.factorydirectlighting.ca>

### Features

#### Housing

Durable extruded aluminum frame with frosted smooth lens. Suitable for dry location applications only. On-body on/off switch is provided for individual control (except 9" models).

#### LED Driver

Fixture is provided with built-in silent non-flicker electronic LED driver, 120V, 60Hz.

#### Light Output

This accent light is available in 3000°K, 4000°K colour temperature.

#### Dimming

Fixture is dimmable with industry standard TRIAC, ELV and Incandescent dimmers.

#### LED Characteristics

Powered by LED integrated strip that maintains uniform intensity with 70% lumens at 50,000 hours average life; with a minimum CRI of 80.

#### Beam Spread

The fixture lens provides for 160° beam spread.

#### Linking

Complete with a joiner, these no shadow linking fixtures can be linked up to 10 units in a single run.

#### Mounting Kit




Hardware provided for mounting fixture to standard horizontal surfaces or vertical wall surface.

#### Operating Temperature

-10°C~40°C (14°F~104°F).

#### SPECIFICATION

Approved Location	Damp
Beam Angle	160°
CCT	3000°K / 4000°K /
Certification	cETLus
Connection Type	3-Wire
CRI	80+
Dimming	Yes
Dimming Technology	TRIAC / ELV / Incandescent
Lumens	759 / 779
Lumens per watt	84 / 87
Max. Operating Temp.	40°C
Min. Start Temp.	-10°C
Lumen Maintenance	70% @ 50,000 hrs
Rated Life	50,000 hrs
Voltage	120V
Warranty	3 Years
Wattage	Up to 5



### Ordering Guide

FDUC-23-9W-LED- Color Temperature K  
30K:3000K  
40K:4000K

#### Accessories

FDUC-HB ( Hardwire Box with Switch )

FDUC-FC ( 6" Flex Connector )

FDUC-PC ( 3 Wire Power Cord )