

# **Pre-Select 5 CCT** 4" Trimless LED Downlight

FDTL-LED-4-15W-5CCT-BK SKU#101075



# **Trim Finish Options**

• BLACK • WHITE



#### **Features**

- \* Durable airtight aluminum body
- \* Type IC, Air-Tight & Wet No Housing Required
- \* Flangeless installation, provide a more high end looking
- \* No housing required, easy and fast installation
- \* 10%-100% dimming capability. This fixture is compatible with industry standard forward-phase / reverse-phase and TRIAC/ELV dimmers
- \* Rated for long life over 50,000 hours

Model	FDTL-LED-4-15W-5CCT-WH / FDTL-LED-4-15W-5CCT-BK
Watts	15W
CRI	80Ra+
Color Temperature(K)	Pre-Select 5 CCT 2700K/3000K/3500K/4000K/5000K
Light Ouput(lm)	1000lm
Default Driver Input	AC120V, 60Hz
Dimming	Triac Dimming 10% - 100%
Power Factor	>0.99
Approved Location	Wet Location
Air Tight	Yes
Operating Temp.	(-4°F~104°F) -20~40°C
Beam Angle	38°

SPECIFICATIONS

PACKAGE	
Weight.(g)	672g
Qty/CTN (pcs)	18 pcs/CTN
Box Dimension	495(L) x 365 (W) x 310(H) mm
Gross Weight	15.12 kg/CTN


















#### **DIMENSIONS**





#### **INCLUDED IN BOX**


- 4" Trimless LED Downlight-15 watts, with Driver
- 4 Screws



### **INSTALLATION**







ACCESSORIES (Optional)

## **Mounting Plates**





2"/3"/3.5"/4" new construction pre-mounting plate opening Ø2-1/8"(54mm), Ø2-7/8"(72mm), Ø3-3/4"(95mm), Ø5-1/4"(132mm)

### Flexible Connector



4ft/ 6ft/ 10ft/ 20ft flexible connector