

4 FT LED Premium Strip

Link to multiple lengths using optional connecters

-	 -		
	1		
	 	_	

FDL 4FT LED Premium Strip is an ideal choice for residential, commercial and industrial lighting with steady performance and long lifetime.

Features


- Voltage: 120-347V
- High Lumen Efficiency: Lumen output more than 130 lm/W, reduces energy consumption up to 80% compared to a fluorescent fixture.
- Pre-Select 3 Wattage 30-38-46W
- Pre-Select 3CCT 3500K-4000K-5000K
- Dimming 0-10V
- cETLus & DLC 5.1 Permium

Dimension

Specification

L	W	H	LF
(mm)	(mm)	(mm)	(mm)
1131	66.5	68.5	870





LF

LF: the length between mounting screw holes

Item	specification	ification FDS-30-38-46-LED-3CCT-120-347V					
		Pre-Select 3 Wattage 30-38-46W & Pre-Select 3CCT 3500K-4000K-5000K					
General		30W	38W	46W			
Performance	Lumens Output	■3500K @ 4200lms ■4000K @ 4500lms ■5000K @ 4260lms	■3500K @ 5130lms ■4000K @ 5510lms ■5000K @ 5206lms	■3500K @ 5980lms ■4000K @ 6440lms ■5000K @ 6072lms			
	Efficacy(Im/w)	≥140 I m/W	≥135lm/W	≥130lm/W			
	CRI	80					
	Lifetime(hours)	50,000					
	Color Consistency	Proprietary binning for uniform color					
	Power Factor	>0.95					
	Input voltage	120-347V					
Physical	Housing	Metal					
	Mounting	Ceiling Mount or Cable Mount					
	Humidity	20%-85% RH, non-condensing					
Certification	Certification	cETLus, DLC 5.1 Premium					
	Work Temperature	-4°F to 122°F (-20°C to +50°C) operating temperature					
	Environment	Damp Location					
	Warranty	5-year Warranty					

Optional Accessories



4 FT Wire Guard SKU#100887

Factory Direct Lighting (2020) Ltd. www.fdlighting.ca Tel: 1-855-533-0743 / 1-905-944-1210







Motion Sensor SKU#100884 Connector SKU#100883 Suspension Kit, 1.5M Chain and 2 pcs V-hooks SKU#100888 100 Shields Court Unit B Markham, Ontario Canada, L3R 9T5